



Senk – Blechschrauben

mit Phillips – Kreuzschlitz, Form H


Countersunk flat head tapping screws with cross recessed (Phillips)



Form "C" mit Spitze



dk	4,3	5,5	6,8	7,5	8,1	9,5	10,8	12,4			
k	1,3	1,7	2,1	2,3	2,5	3	3,4	3,8			

		d	2,2	2,9	3,5	3,9	4,2	4,8	5,5	6,3			
l	6,5	5,70	3,80	5,20	5,90								
	9,5	5,20	2,70	3,50	4,10	4,70	5,90						
	13	5,20	2,80	3,70	4,10	4,80	6,10	9,80	13,40				
	16	6,40	3,00	3,90	4,40	5,30	6,60	10,50	11,30				
	19	6,70	3,20	4,20	4,90	5,80	7,30	11,20	12,10				
	22	8,70	5,40	5,30	6,00	6,60	8,40	12,30	13,30				
	25	10,80	5,60	5,50	6,20	6,80	8,60	13,20	14,10				
	32	11,80	7,70	6,30	7,30	8,40	10,90	15,40	16,90				
	38		12,30	7,00	8,40	9,50	12,20	17,40	18,70				
	45			9,90	10,40	13,70	15,90	20,70	22,30				
	50			11,10	11,20	15,60	16,40	23,20	26,00				
	55						20,50	27,60					
	60			12,60	24,60	24,60	20,50	27,60	32,70				
	70			13,60	32,80	31,80	26,60	36,80	39,90				
80					33,70	34,80	42,50	45,50					
90					38,60	40,40	50,10	63,90					
100					58,60	61,40	66,00	90,00					
120						85,60	189,00						
	1.000	1.000	1.000 ab 32 L 500	1.000 ab 32 L 500	1.000 ab 32 L 500	500 ab 32 L 200	200 ab 32 L 100	200 ab 32 L 100					

Preise in € per 100 Stück brutto, o. MWSt. Alle Maße in mm. Weitere Abmessungen auf Anfrage!



Auch aus Lagervorrat lieferbar: Form F - mit TX Antrieb (WS 9478)
s. Seite 394 - als Sicherheitsschraube (WS 9486) s. Seite 401.
Preise für Form "SB" auf Anfrage!